CUTTING POLYGONS TO ACHIEVE SEPARABILITY, WITH DYNAMIZATION

FRANK DEHNE

School of Computer Science, Carleton University, Ottawa, Canada K1S 5B6

ROBERTO TAMASSIA

Department of Computer Science, Brown University, Providence, RI 02912, USA

Abstract

Let P={p₁, ..., p_m} be a set of m disjoint simple polygons in the plane with a total of n vertices. A polygon pi is separable from P in a direction d if pi can be translated to infinity in direction d without colliding with any other polygon pi of P. Set P is separable in direction d, if there is a permutation $(p_{a(1)}, p_{a(2)}, ..., p_{a(m)})$ such that $p_{a(i)}$ is separable from $\{p_{a(i+1)}, ..., p_{a(m)}\}$, for i=1,...,m-1. In this paper we further investigate the separability problem. We consider the case that other circumstances require that the polygons be sequentially separated in only one given direction d. For example, consider a crane that has to lift a set of objects, one object at a time, out of a deep shaft. If separability is not possible in direction d, the polygons have to be cut in order to allow them to be separated. The process of cutting a polygon pi is represented by introducing a new edge, parallel to direction d, that splits pi into two disjoint polygons. We investigate the problem of determining a minimum set of cuts that achieve separability in direction d.

Our approach is based on a new geometric construction, the obstruction multigraph of P in direction d, denoted by Gd(P). This multigraph is defined as follows: The vertices of Gd(P) are the polygons of P, plus two special vertices, s and t, which are associated with two fictitious polygons ps and pt at plus infinity and minus infinity in direction d, respectively. (Any polygon of P would collide with either ps or pt when moved in direction -d or +d by an arbitrary distance.) The edges incident to a vertex pi are obtained by following the boundary of polygon pi in clockwise direction. During the traversal, we add an outgoing edge from p_i to another polygon p_i whenever polygon p_i sees a new polygon pi in direction d from the current position; similarly, we add an incoming edge from another polygon pk to pi whenever polygon pi is seen by a new polygon pk in direction d, at the current position. Gd(P) is a directed, planar multigraph with O(n) edges and has exactly one source and one sink; it can be constructed in O(n log n) time.

For every node p_i of $G_d(P)$ representing a polygon p_i of P, let $E(p_i)=(e_1, ..., e_k)$ be the circular sequence of incoming and outgoing edges of p_i . Furthermore, let $ZO(p_i)=(z_1, ..., z_k)$ be the 0-1sequence of p_i , where $z_i=1$ if e_i is an incoming edge and $z_i=0$ if e_i is an outgoing edge $(1 \le j < \le k)$. A node pi of Gd(P) is called bitonic if and only if its 0-1-sequence ZO(pi) is bitonic. A fundamental property of G_d(P) is that the separabilty of P in a direction d can be verified locally at each vertex. We show that P is separable in direction d if and only if every vertex of Gd(P) is bitonic.

The obstruction multigraph allows a minimum set of cuts to be determined efficiently. We show that the minimum number of cuts of polygons of P necessary to achieve separability in direction d is equal to the minimum number of splits necessary to transform the 0-1-sequences of non-bitonic vertices of Gd(P) into bitonic sequences; any minimum cut set for the polygons is associated with a minimum set of cuts of non-bitonic 0-1 sequences (but not every cut of a 0-1-sequence corresponds to a feasable polygon cut). A minimum cut set can be computed in O(n log log n) time using the internal visibility graph (see Tarjan and Van Wyk's algorithm) of each polygon in direction d. Summarizing, we obtain that a minimum set of cuts of polygons of P that achieve separability in direction d can be found in O(n log n) time using O(n) space.

The fact that separability and a minimum cut set can be determined locally at every node of the obstruction multigraph allows an efficient dynamization for decompositions and small translations of individual polygons (without collisions). Clearly, only translations orthogonal to the direction d affect the separability of the the polygon set. An elementary translation of a polygon pi with respect to direction d is a translation of pi that alters at most O(1) edges of the obstruction graph G_d(P). Besides elementary translations, we also consider the decomposition of a polygon by means of a vertical cut, or gluing two polygons that share some vertical portion of the boundary. We show that the obstruction graph G_d(P) and the minimum number of polygon cuts that achieve separability in direction d can be

updated in time O(log n) after an elementary translation or cut/glue operation.